Copying/Moving a message in IMAP account	1	2	3	4	5	6	7	8	9	10	11	12
Source folder is in online mode	Y	Y	Υ	Y	N	N	N	N	N	N	N	N
Destination folder is in online mode	Y	Y	N	N	Y	Y	Y	Y	N	N	N	N
TB is in online state	Y	N	Υ	N	Y	Y	N	N	Y	Y	N	N
Message is available locally	-	-	-	-	Y	N	Y	N	Y	N	Y	N
ACTIONS												
- Remove the header from the source folder's database	<b>X</b> <sup>2</sup>											
- Add the new header into the destination folder's database	<b>X</b> <sup>1</sup>	X	<b>X</b> <sup>1</sup>	х	<b>X</b> <sup>1</sup>	<b>X</b> <sup>1</sup>	Х	х	<b>X</b> <sup>1</sup>	<b>X</b> <sup>1</sup>	X	х
- Copy the message into destination folders' mbox		Х					Х				X	

<sup>1</sup> if and only if the destination folder is already selected (has connection to the server) 2 Do not remove if operation is COPY

DELETE and MOVE are the same operations if DELETE means move to Trash

Select a message	1	2	3	4
Message folder is online	Y	Y	Z	N
TB is in online state	Y	N	Y	N
ACTIONS				
- Fetch message from the server	X	ı	X	-
- Get local copy if available		х		х
- Store locally in the folder's <b>mbox</b>			х	

Tag a message	1	2	3	4
Message folder is online	Y	Y	N	N
TB is in online state	Υ	N	Υ	N
ACTIONS				
- Store flag in	server	local db	server	local db

Select a folder	1	2	3	4
Folder is online	Y	Y	N	N
TB is in online state	Y	N	Y	N
ACTIONS				
- Fetch message headers from the server - Remove headers with IDs do not exist on the server - Add new headers to the local database	x		x	
- Playback offline operations	<b>X</b> <sup>1</sup>		<b>X</b> <sup>1</sup>	
- Fetch headers from the local database		X		х

<sup>1</sup> if there is any pending operation where this folder is the source folder